

# JC10M Series


High Resolution FA/MV Lenses

## Features of JC10M Series

- ▶ 200lp/mm center resolution and low distortion maximize performance of high-end inspection.
- ▶ Incorporating Kowa's wide-band coating and floating mechanism system, the JC10M lens series greatly reduces chromatic aberration from close distance to infinity and maintains a high transmission from visible to NIR.
- ▶ Short minimum object distance and compact design using aspherical lenses (5 models/f=5~25mm) allow for easy installation in compact machine vision systems.




LM5JC10M




Model	LM5JC10M
Focal Length(mm)	5
Image Size(mm)	8.8×6.6(Φ11)
Iris Range(F-stop)	F1.8-F16
Focusing Range(m)	0.1-∞
Control	Manual
Focus	Manual
Shooting Range at M.O.D.(mm)	197.0(H)×147.0(V)
Angle of View	2/3 Inch 62.2×66.5
(Degrees)	1/1.8 Inch 71.1×56.5
1/2 Inch	64.9×51.1
Resolution(Center, Corner)	200lp/mm, 160lp/mm
TV Distortion(%)	-0.33
Back Focus in Air(mm)	10.3
Mount	C-mount
Filter Thread(mm)	M46×P0.75
Size(mm)	Φ38×59.4
Weight(g)	120
Temperature Range	-10°C~+50°C

LM8JC10M




2/3" 1/1.8" 1/2" 8.5mm  
 FIXED OMEGA C-MT METAL LO-DIS FLOAT XD  
 Fixed Focal Megapixel C-mount Metal Body Low Distortion Floating Extra Low Dispersion

LM12JC10M




2/3" 1/1.8" 1/2" 12mm  
 FIXED OMEGA C-MT METAL LO-DIS FLOAT XD  
 Fixed Focal Megapixel C-mount Metal Body Low Distortion Floating Extra Low Dispersion

LM16JC10M




2/3" 1/1.8" 1/2" 16mm  
 FIXED OMEGA C-MT METAL LO-DIS FLOAT  
 Fixed Focal Megapixel C-mount Metal Body Low Distortion Floating

LM25JC10M




2/3" 1/1.8" 1/2" 25mm  
 FIXED OMEGA C-MT METAL LO-DIS FLOAT  
 Fixed Focal Megapixel C-mount Metal Body Low Distortion Floating

LM35JC10M



2/3" 1/1.8" 1/2" 35mm  
 FIXED OMEGA C-MT METAL LO-DIS FLOAT  
 Fixed Focal Megapixel C-mount Metal Body Low Distortion Floating

LM50JC10M



2/3" 1/1.8" 1/2" 50mm  
 FIXED OMEGA C-MT METAL LO-DIS FLOAT XD  
 Fixed Focal Megapixel C-mount Metal Body Low Distortion Floating Extra Low Dispersion

Model	LM8JC10M	LM12JC10M	LM16JC10M	LM25JC10M	LM35JC10M	LM50JC10M
Focal Length(mm)	8.5	12	16	25	35	50
Image Size(mm)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)
Iris Range(F-stop)	F1.8-F22	F1.8-F11	F1.8-F16	F1.8-F16	F2.0-F16	F2.8-F16
Focusing Range(m)	0.1-∞	0.1-∞	0.1-∞	0.1-∞	0.1-∞	0.1-∞
Control	Manual	Manual	Manual	Manual	Manual	Manual
Focus	Manual	Manual	Manual	Manual	Manual	Manual
Shooting Range at M.O.D.(mm)	133.2(H)×99.6(V)	80.7(H)×60.2(V)	61.1(H)×45.7(V)	36.7(H)×27.5(V)	23.4(H)×17.6(V)	19.1(H)×14.3(V)
Angle of View	2/3 Inch 54.0×41.9	39.1×29.8	30.0×22.7	20.0×15.1	14.3×10.8	10.1×7.6
(Degrees)	1/1.8 Inch 45.3×34.8	32.4×24.6	24.7×18.6	16.4×12.3	11.7×8.8	8.2×6.1
1/2 Inch	40.8×31.2	28.9×21.9	22.0×16.6	14.6×11.0	10.4×7.8	7.3×5.5
Resolution(Center, Corner)	200lp/mm, 160lp/mm	200lp/mm, 160lp/mm	200lp/mm, 160lp/mm	200lp/mm, 160lp/mm	200lp/mm, 160lp/mm	200lp/mm, 160lp/mm
TV Distortion(%)	0.31	-0.12	-0.20	-0.09	0.05	-0.02
Back Focus in Air(mm)	12.1	13.9	14.6	17.9	14.2	12.8
Mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount
Filter Thread(mm)	M34×P0.5	M25.5×P0.5	M25.5×P0.5	M25.5×P0.5	M34×P0.5	M30.5×P0.5
Size(mm)	Φ36×56.0	Φ33×53.5	Φ33×47.5	Φ33×45.5	Φ43×49	Φ38×77
Weight(g)	115	105	90	95	160	170
Temperature Range	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C

### Diagram of M.O.D. / Magnification Using A Close Up Ring

Model	LM8JC10M	LM12JC10M	LM16JC10M	LM25JC10M	LM35JC10M	LM50JC10M
(Non)MOD/Magnification	100mm/0.05×	100mm/0.07×	100mm/0.11×	100mm/0.15×	100mm/0.24×	100mm/0.46×
1mm Ring/M.O.D./Magnification	-	20mm/0.20×	48mm/0.19×	61mm/0.21×	79mm/0.28×	85mm/0.40×
5mm Ring/M.O.D./Magnification	-	-	-	18mm/0.45×	46mm/0.44×	65mm/0.50×
10mm Ring/M.O.D./Magnification	-	-	-	-	29mm/0.63×	49mm/0.62×
20mm Ring/M.O.D./Magnification	-	-	-	-	-	31mm/0.87×

† Images may differ from the actual product.

† Images may differ from the actual product.