




Asahi AFP 1216 processing equipments

Systems for flexo platemaking



Model	Plate size	Description	Weight & Size
 Single Exposure 1216 EHQ	120 x 160 cm 47 x 63 inch	Exposure frame with temperature controlled bed. Automatic pneumatic lid. PLC control with color touch screen display. Light integrator for automatic compensation of UV output variation. Seconds and mJ mode. Lamps temperature regulation. High & consistent UV output to guarantee plate exposure consistency.	890 kgs 265 x 172 x 110 cm (open 238 cm) 104 x 68 x 43 inch (open 94 inch)
 Dryer 1216 D	120 x 160 cm 47 x 63 inch	Drying unit with 6 drawers. The unit consists of 3 dryers of 2 drawers each. Each dryer with separate heating system, blowers, control and regulation. Drawers closing system with magnetic sealing (no fume leakage). Large gap between drawer and frame for easy plate introduction. High airflow, consistent and uniform temperature.	650 kgs 208 x 172 x 110 cm 82 x 68 x 43 in
 Light Finisher 1216 LF	120 x 160 cm 47 x 63 inch	Light finishing unit including UVA & UVC lamps. All lamps fitted with electronic ballasts. The unit can be placed on top of the 1216 D dryer. High airflow exhaust system.	320 kgs 208 x 172 x 33 c

Asahi Photoproducts
(Europe) n.v./s.a.
Paepsem Business Park
Boulevard Paepsem 22
1070 Brussels/Belgium
Tel.: 00 32-2-5 26 05 30
Fax: 00 32-2-5 26 05 45
www.asahi-photoproducts.com

This brochure provides information about our products and their applications according to the present state of our technology. It does not guarantee any specific properties or suitabilities of the products for concrete applications. Existing commercial property rights and regulations must be observed. Subject to modification.

www.asahi-photoproducts.com

