



Asahi AFP 1321 Processing equipments





Systems for flexo platemaking

Model	Plate size	Description	Weight & Size
 <p>Dryer 1321 D</p>	132 x 203 cm 52 x 80 inch	Drying unit with 6 drawers. The unit consists of 3 dryers of 2 drawers each. Each dryer with separate heating system, blowers, control and regulation. Drawers closing system with magnetic sealing (no fume leakage). Large gap between drawer and frame for easy plate introduction. High airflow, consistent and uniform temperature.	750 kgs 250 x 165 x 110 cm 98 x 65 x 43 inch
 <p>Light Finisher 1321 LF</p>	132 x 203 cm 52 x 80 inch	Light finishing unit including UVA & UVC lamps. All lamps fitted with electronic ballasts. The unit can be placed on top of the 1321 D dryer. High airflow exhaust system.	400 kgs 250 x 185 x 33 cm 98 x 73 x 13 inch

Asahi AFP 1321 processing equipments

Systems for flexo platemaking



Model	Plate size	Description	Weight & Size
 <p>Single Exposure 1321 EHQ</p>	132 x 203 cm 52 x 80 inch	Exposure frame with temperature controlled bed. Automatic pneumatic lid. PLC control with color touch screen display. Light integrator for automatic compensation of UV output variation. Seconds and mJ mode. Lamps temperature regulation. High & consistent UV output to guarantee plate exposure consistency.	1 300 kgs 336 x 210 x 105 cm (open 260 cm) 132 x 83 x 41 inch (open 102 inch)
 <p>Double Exposure 1321 ETL</p>	132 x 203 cm 52 x 80 inch	Exposure unit with hydraulic vertical opening lid. Double side exposure with automatic shutter. Lamps temperature control and regulation. Light integrator for automatic UV variation compensation for back and main exposure. 2 storage drawers.	1 400 kgs 305 x 221 x 119 cm (open 200 cm) 120 x 87 x 47 inch (open 79 inch)
 <p>Double Exposure 1321 ESL</p>	132 x 203 cm 52 x 80 inch	Exposure unit with pneumatic shell opening lid. Double side exposure with automatic shutter. Lamps temperature control and regulation. Light integrator for automatic UV variation compensation for back and main exposure. 2 storage drawers.	1 400 kgs 305 x 221 x 119 cm (open 200 cm) 120 x 87 x 47 inch (open 79 inch)
 <p>Processor 1321 DP</p>	132 x 203 cm 52 x 80 inch	Automatic flowline processor with double hydraulic and tank system to allow separation of digital black layer from washout solvent. Unique washout brushing system with rotating brushes and double lateral alternate oscillating movement. PLC control with color touch screen display. Specific maintenance program in software. Integrated solvent heater chiller and solvent saturation analyser with automatic replenishment.	1 340 kgs 208 x 457 x 100 cm 82 x 180 x 41 inch

